



SAFE-LIFT CORP. Miami, Florida

# FORGED EYE BOLTS



Shank Diam. and Length (in)	Length Of Thread (In)	Eye Dim.		Working Load Limit (lbs)
		I.D. (In)	O.D. (In)	
1/4 x 2	1 1/2	1/2	1	500
1/4 x 4	2 1/2	1/2	1	500
5/16 x 2 1/4	1 1/2	5/8	1 1/4	800
5/16 x 4 1/4	2 1/2	5/8	1 1/4	800
3/8 x 2 1/2	1 1/2	3/4	1 1/2	1,200
3/8 x 6	2 1/2	3/4	1 1/2	1,200
1/2 x 3 1/4	1 1/2	1	2	2,200
1/2 x 6	3	1	2	2,200
1/2 x 8	3	1	2	2,200
1/2 x 10	3	1	2	2,200
1/2 x 12	3	1	2	2,200
5/8 x 4	2	1 1/4	2 1/2	3,500
5/8 x 6	3	1 1/4	2 1/2	3,500
5/8 x 8	3	1 1/4	2 1/2	3,500
5/8 x 10	3	1 1/4	2 1/2	3,500
5/8 x 12	4	1 1/4	2 1/2	3,500
5/8 x 15	5	1 1/4	1 1/2	3,500
5/8 x 18	5	1 1/4	1 1/2	3,500
3/4 x 4 1/2	2	1 1/2	3	5,200
3/4 x 6	3	1 1/2	3	5,200
3/4 x 8	3	1 1/2	3	5,200
3/4 x 10	3	1 1/2	3	5,200
3/4 x 12	4	1 1/2	3	5,200
3/4 x 15	5	1 1/2	3	5,200
7/8 x 5	2 1/2	1 3/4	3 1/2	7,200
7/8 x 8	4	1 3/4	3 1/2	7,200
7/8 x 12	4	1 3/4	3 1/2	7,200
1 x 6	3	2	4	10,000
1 x 9	4	2	4	10,000
1 x 12	4	2	4	10,000
1 x 18	7	2	4	10,000