










SAFE-LIFT CORP. Miami, Florida

WIRE ROPE

	Size (ins.)	Approx. Breaking Strength (lbs.)		Approx. Wt./ 100 Ft. (lbs.)	
		6 x 19 Class	6 x 37 Class		
6 x 19 Fiber Core 	Bright Fiber Core Wire Rope	3/16	3,100	—	6
		1/4	5,480	—	11
		5/16	8,520	—	16
		3/8	12,200	12,200	24
		7/16	16,540	—	32
		1/2	21,400	21,400	42
		9/16	27,000	—	53
6 x 37 Fiber Core 		5/8	33,400	33,400	66
		3/4	47,600	47,600	95
	Bright IWRC Wire Rope	1/4	5,891	—	12
		5/16	9,159	—	18
		3/8	13,110	13,110	26
	6 x 19	7/16	17,780	—	35
	6 x 25 fi	1/2	23,000	23,000	46
6 x 26 WS	9/16	29,000	—	59	
6 x 37	5/8	35,400	35,800	72	
6 x 19 IWRC 		3/4	51,200	51,200	104
		7/8	69,200	—	142
		1	89,800	—	185
	Swaged IWRC Wire Rope	*1/2	31,600	—	55
		*9/16	39,600	—	71
		*5/8	49,000	—	86
		6 x 26	*3/4	70,000	—
* finished diameter	*7/8	94,600	—	184	
6 x 37 IWRC 	Bright IWRC Wire Rope	3/8	11,180	—	25
		1/2	19,700	—	45
		5/8	30,600	—	71
	19 x 7 NR	3/4	43,600	—	102
Swaged 6 x 26 IWRC 	Stainless IWRC Wire Rope	7/16	16,300	—	36
		1/2	22,800	—	46
		5/8	35,000	—	72
	6 x 25 fi	3/4	49,600	—	104
19 x 7 NR IWRC 	Stainless 6 x 25 fi IWRC 	Wire Rope			
		<ul style="list-style-type: none"> • Reels: 500 ft., 1,000 ft., and 5,000 ft. Custom lengths on request. • Preformed, Right Regular Lay, Improved Plow Steel. • 6 x 19 Class: 6 x 19 6 x 25 fi (Filler Wire) 6 x 26 WS (Warrington-Seale) • 6 x 37 Class: 6 x 36 6 x 37 6 x 41 • Fiber Core (FC) and Independent Wire Rope Core (IWRC). • Bright, Galvanized, Stainless and Swaged Wire Rope. 			